Glenmarc	Industries Inc.	2001 S. Blue Island Ave Chicago IL 60608
----------	-----------------	--

312-243-0800 fax 312-243-4670 email: info@glenmarc.com www.glenmarc.com

Material Safety Data Sheet

Date	03/01/2005
Dale	03/01/2003

SECTION 1____

MANUFACTURER: Glenmarc Industries Inc. 2001 S. Blue Island Ave. Chicago IL 60608

PRODUCT NAME: GER3002 RESIN Emergency Phone: 800-255-3924 Chemtel Non-emergency Phone: 800-323-5350

HAZARD RATINGS: Fire: 1 Health: 2 Reactivity: 0

CHEMICAL NAME: Bisephenol A/Epichlorohydrin Based Epoxy Resin CHEMICAL FAMILY: Epoxy Resin

Toxicity Data:

Oral LD-50 (rat)=> 11.4g/kg (mouse)=>15.6/kg Dermal LD-50 (rbt)=6.5g/kg

Acute inhalation LC50—no deaths in Sat'd air, 8 hr.* *This inhalation test may be relevant due to low volatility of the resin. (See section 7)

SECTION 3 Health Information_____

Eye contact: Can cause moderate irritation

Skin contact: Moderately irritating to skin. Prolonged or repeated skin exposure may result in Sensitization.

Inhalation: Because of its low volatility (see section 7) this product is not likely to be an inhalation hazard. Ingestion: Based on testing product is considered to have a low order of acute oral toxicity.

SECTION 4 Occupational exposure limits

None established

SECTION 5 Emergency and First Aide Procedures_____

Eye Contact: Flush with water for 15 minutes while holding eyelids open. Contact Physician. Skin Contact: Wash with soap and water. Remove contaminated clothing and shoes. Do not

Reuse until cleaned. If persistent irritation occurs. Contact Physician.

Inhalation: Remove to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not Breathing. Contact physician.

Ingestion: Do not induce vomiting. In general, no treatment is necessary unless large quantities of product is ingested. Contact physician.

SECTION 6 Physical data_____ Boiling point: >500F Melting point: n/a Specific Gravity: (water=1) 1.17 Evaporation rate: n/a Flammable limits/%Volume in Air lower----- Upper_____ Solubility in Water: negligible Vapor pressure: 0.03@77C Appearance and Odor: Very light yellow, very viscous

SECTION 7 Fire and Explosion Hazards______ Flash point and method used: <200F (COC) Lower flammable limit: n/a Upper flammable limit: n/a Extinguishing Media: CO2, dry chemicals, water fog, foam

Special Fire Fighting Procedures and Precautions: Material will not burn unless preheated. Do not enter confined fire space without proper protective equipment including a NIOSH approved self-contained breathing apparatus. Cool fire-exposed containers with water.

SECTION 8 Reactivity_____

Stability: Stable Hazardous Polymerization: Will not occur

Conditions and Materials to avoid:

Can react vigorously with strong oxidizing agents and strong Lewis or mineral acids. Avoid amines and bases. In reactions with many curing agents, considerable heat is released.

Hazardous Decomposition Products:

Carbon monoxide, aldehydes and acids may be formed during combustion. Reaction with some curing agents may produce considerable heat.

SECTION 9 Employee Protection_____ Respiratory protection: Not ordinarily required Protective clothing: Wear impervious gloves and protective clothing as required to prevent skin contact. Wear chemical goggles to prevent eye contact.

Additional Preventive Measures:

Ventilation is required for mixing, application, and curing operations to control vapor concentrations, particularly for processes involving heat. Eye wash fountains should be available for emergency use.

SECTION 10 Environmental Protection

Spill or leak procedures:

May burn although not readily ignitable. Use cautious judgment when cleaning up large spills.

Large spills:

Ventilate area. Wear protective clothing, shoes and eye protection. Shut off sources of leak if safe to do so. Dike and contain. Absorb spill with absorbent material and place in closed container.

Small spills: Take up with an absorbent material and dispose of properly.

Handle in accordance with the potential of the curing agent used.

Waste disposal: Place in appropriate disposal facility incompliance with local regulations. For further information: Contact EPA-RCRA Hotline 800-424-9346 Environmental Hazards: _____

SECTION 11 Special Precautions_

Keep container tightly closed. Store in cool, dry place. Wash with soap and water before eating, drinking, smoking or using toilet facilities. Launder contaminated clothing before reuse.

SECTION 12 Transportation Requirements_

Not Hazardous by D.O.T. regulations D.O.T. proper shipping name: not regulated Other requirements: none

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk to his use of the material.